

Product Data Sheet
TerraTex NO4 w/ Commercial 2" x 4" 24" x 100'
Austin Spec Silt Fence (43067)

Assembled Unit Components

Geotextile Fabric: TerraTex NO4
Fabric Height: 36 in
Support Wire: Welded Wire
Height: 24"
Gauge: 15ga
Opening Size: 2" x 4"
Zinc Coating: Class 1
Unit Length: 100 ft

Hanes Geo Components preassembled silt fence is TerraTex NO4 with 24" 2" x 4" 15ga welded wire and is assembled in the USA. TerraTex NO4 is a non-woven geotextile made up of polypropylene fibers that are needed to form stable and durable structure, which allows the fibers to maintain their relative position. It is non-biodegradable and resistant to ultraviolet degradation, rotting, and most soil chemicals.

PROPERTY	TEST METHOD	MARV English
Tensile Strength	ASTM D4632	90 lbs.
Trapezoid Tear	ASTM D4533	40 lbs.
Elongation	ASTM D4632	50%
Puncture Resistance	ASTM D4833	70 lbs.
CBR Puncture	ASTM D6241	265 lbs.
Mullen Burst	ASTM D3786	240 psi
UV Resistance (500 hrs)	ASTM D4355	70%
Apparent Opening Size (AOS)**	ASTM D4751	50 US Std.Sieve
Permittivity	ASTM D4491	2.0 sec ⁻¹
Water Flow Rate	ASTM D4491	150 gpm/ft ²

***DISCLAIMER:** Descriptions regarding the products described herein are based solely upon information provided by the manufacturer and are provided for informational purposes only. NOTHING CONTAINED HEREIN SHOULD BE CONSTRUED AS CREATING AN EXPRESSED OR IMPLIED WARRANTY, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS, EACH OF WHICH IS HEREBY DISCLAIMED. THERE ARE NO WARRANTIES THAT EXTEND BEYOND THE DESCRIPTION ON THE FACE HEREOF. The final determination as to the suitability of any product of Hanes Geo Components in any particular application rests solely with the user. Hanes Geo Components reserves the right to alter or modify its products and descriptions at any time without notice.