

Product Data Sheet
TerraTex NO6 w/ Commercial 2" x 4" 24" x 100'
Austin Spec Silt Fence (43066)

Assembled Unit Components

Geotextile Fabric: TerraTex NO6
Fabric Height: 36 in
Support Wire: Welded Wire
Height: 24"
Gauge: 15ga
Opening Size: 2" x 4"
Zinc Coating: Class 1
Unit Length: 100 ft

Hanes Geo Components preassembled silt fence is TerraTex NO6 with 24" 2" x 4" 15ga welded wire and is assembled in the USA. TerraTex NO6 is a non-woven geotextile made up of polypropylene fibers that are needed to form stable and durable structure, which allows the fibers to maintain their relative position. It is non-biodegradable and resistant to ultraviolet degradation, rotting, and most soil chemicals.

| PROPERTY | TEST METHOD | MARV English |
|-------------------------------|-------------|-------------------------|
| Tensile Strength | ASTM D4632 | 160 lbs. |
| Trapezoid Tear | ASTM D4533 | 65 lbs. |
| Elongation | ASTM D4632 | 50% |
| Puncture Resistance | ASTM D4833 | 90 lbs. |
| CBR Puncture | ASTM D6241 | 410 lbs. |
| Mullen Burst | ASTM D3786 | 315 psi |
| UV Resistance (500 hrs) | ASTM D4355 | 70% |
| Apparent Opening Size (AOS)** | ASTM D4751 | 70 US Std.Sieve |
| Permittivity | ASTM D4491 | 1.6 sec ⁻¹ |
| Water Flow Rate | ASTM D4491 | 110 gpm/ft ² |

***DISCLAIMER:** Descriptions regarding the products described herein are based solely upon information provided by the manufacturer and are provided for informational purposes only. NOTHING CONTAINED HEREIN SHOULD BE CONSTRUED AS CREATING AN EXPRESSED OR IMPLIED WARRANTY, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS, EACH OF WHICH IS HEREBY DISCLAIMED. THERE ARE NO WARRANTIES THAT EXTEND BEYOND THE DESCRIPTION ON THE FACE HEREOF. The final determination as to the suitability of any product of Hanes Geo Components in any particular application rests solely with the user. Hanes Geo Components reserves the right to alter or modify its products and descriptions at any time without notice.